

Page: 1/4

Revised edition no: 1

Date: 15/7/2005

Supersedes: 0/0/0

Hydrogen

AL067A





flammable

IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Trade name : Hydrogen **MSDS No** : AL067A Chemical formula : H2

Company identification : AIR LIQUIDE SA

France

See paragraph 16 "OTHER INFORMATION"

: See paragraph 16 "OTHER INFORMATION" **Emergency phone nr**

2 COMPOSITION / INFORMATION ON INGREDIENTS

: Substance. **Substance / Preparation**

Substance name Contents **CAS No** EC No Index No Classification 100 % 1333-74-0 Hydrogen 215-605-7 001-001-00-9 F+: R12

Contains no other components or impurities which will influence the classification of the product.

3 HAZARDS IDENTIFICATION

Hazards identification Compressed gas. Extremely flammable.

4 FIRST AID MEASURES

First aid measures

- Inhalation : In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing

apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if

breathing stopped.

: Ingestion is not considered a potential route of exposure. - Ingestion

5 FIRE-FIGHTING MEASURES

Flammable class : Extremely flammable.

Specific hazards : Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products

Extinguishing media

: None.

- Suitable extinguishing media

Specific methods

: All known extinguishants can be used.

: If possible, stop flow of product.

Move away from the container and cool with water from a protected position. Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/

explosive re-ignition may occur. Extinguish any other fire.

fighters

Special protective equipment for fire : In confined space use self-contained breathing apparatus.

AIR LIQUIDE SA



Page : 2 / 4

Revised edition no : 1

Date : 15/7/2005

Supersedes : 0/0/0

Hydrogen

AL067A

6 ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear self-contained breathing apparatus when entering area unless atmosphere is

proved to be safe. Evacuate area.

: Try to stop release.

Ensure adequate air ventilation. Eliminate ignition sources.

Environmental precautions

Clean up methods : Ventilate area.

7 HANDLING AND STORAGE

Storage : Keep container below 50°C in a well ventilated place.

Segregate from oxidant gases and other oxidants in store.

Handling : Ensure equipment is adequately earthed.

Suck back of water into the container must be prevented.

Purge air from system before introducing gas. Do not allow backfeed into the container.

Use only properly specified equipment which is suitable for this product, its supply

pressure and temperature. Contact your gas supplier if in doubt. Keep away from ignition sources (including static discharges).

Refer to supplier's container handling instructions.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection : Ensure adequate ventilation.

Do not smoke while handling product.

9 PHYSICAL AND CHEMICAL PROPERTIES

Physical state at 20 °C : Compressed gas.

Colour : Colourless.

Odo(u)r : None.

Molecular weight : 2

Melting point [°C] : -259

Boiling point [°C] : -253

Critical temperature [°C] : -240

Vapour pressure, 20°C : Not applicable.

Relative density, gas (air=1) : 0.07
Relative density, liquid (water=1) : 0.07
Solubility in water [mg/l] : 1.6
Flammability range [vol% in air] : 4 to 75
Auto-ignition temperature [°C] : 560

Other data : Burns with a colourless invisible flame.

10 STABILITY AND REACTIVITY

Stability and reactivity : Can form explosive mixture with air.

May react violently with oxidants.



Page: 3 / 4

Revised edition no : 1

Date : 15/7/2005

Supersedes: 0/0/0

Hydrogen

AL067A

11 TOXICOLOGICAL INFORMATION

Toxicity information: No known toxicological effects from this product.

12 ECOLOGICAL INFORMATION

Ecological effects information: No known ecological damage caused by this product.

13 DISPOSAL CONSIDERATIONS

General : Do not discharge into areas where there is a risk of forming an explosive mixture

with air. Waste gas should be flared through a suitable burner with flash back

arrestor

Do not discharge into any place where its accumulation could be dangerous.

Contact supplier if guidance is required.

14 TRANSPORT INFORMATION

UN No. : 1049 **H.l. nr** : 23

ADR/RID

- Proper shipping name : HYDROGEN, COMPRESSED

- ADR Class
: 2
- ADR/RID Classification code : 1 F

- Labelling ADR : Label 2.1 : flammable gas.

Other transport information : Avoid transport on vehicles where the load space is not separated from the driver's

compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what

to do in the event of an accident or an emergency.

Before transporting product containers :
- Ensure that containers are firmly secured.

- Ensure cylinder valve is closed and not leaking.

- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

- Ensure valve protection device (where provided) is correctly fitted.

- Ensure there is adequate ventilation.

- Compliance with applicable regulations.

15 REGULATORY INFORMATION

EC Classification : Index No : 001-001-00-9

F+; R12

EC Labelling

Symbol(s)R Phrase(s)F+: Extremely flammableR12: Extremely flammable.

- S Phrase(s) : S9 : Keep container in a well-ventilated place.

S16 : Keep away from sources of ignition - No smoking.S33 : Take precautionary measures against static discharges.

16 OTHER INFORMATION

Ensure all national/local regulations are observed.

Ensure operators understand the flammability hazard.

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

AIR LIQUIDE SA



Page: 4/4 Revised edition no: 1

Date: 15/7/2005 Supersedes: 0/0/0

Hydrogen

AL067A

16 OTHER INFORMATION (continued)

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws.

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Recommended uses and restrictions: This SDS is for information purposes only and is subject to change without notice. Prior to purchase of products, please contact your local AIR LIQUIDE office for a complete SDS (with Manufacturer's name and emergency phone number).]

End of document